

Self Regulating Heating Cable

11B (FBL-CP)



10 YEAR
Product Warranty

TRACELEC 
HEATING SOLUTIONS

11B (FBL-CP)

SELF REGULATING HEATING CABLE

1. DESCRIPTION




11B self-regulating heating cables provide a power that varies depending on the process temperature. When the temperature drops, the emitted power increases. When the temperature increases, the power of the cable decreases. This prevents hot spots when two cables overlap. This system also adjusts for temperature variations due to stagnant fluids and height differences (vertical pipes).

11B cables are commonly used to maintain temperatures of up to 65°C in pipes, tanks, etc. Exposure to aqueous inorganic chemicals.

2. CABLE SELECTION

Model	Nominal power	Temperature	Voltage
11B102	10 ~ 14 W/m	10°C	230 Vac
11B162	16 ~ 20 W/m	10°C	230 Vac
11B242	24 ~ 28 W/m	10°C	230 Vac
11B302	30 ~ 34 W/m	10°C	230 Vac

3. CONSTRUCTION



Parts	Construction	Material	Notes
1	Conductors	Nickel-Plated Copper	7/0.45, 1.1mm ²
2	Heating element	Polyolefin + C/B	
3	Inner insulation	FR Polyolefin	
4	Ground braid	Copper ground braid	8/0.18*16, Coverage: 70%
5	Outer jacket	FR Polyolefin	

11B (FBL-CP)

SELF REGULATING HEATING CABLE

4. FEATURES

- Cables can be overlapped without creating hot spots or causing a burn out
- It automatically adjusts heat output based upon exposure temperature
- It can be cut to any length in the field
- It adjusts its output to independently respond to ambient temperatures all along its length
- Energy efficiency which extends the life of the cable
- Connection and end termination kits easy to install

5. USE

11B heating cables are mainly used for:

- Water lines freeze protection
- Industrial maintenance temperature
- Ordinary and hazardous locations (Ex e IIC Gb, ATEX certification)


6. SPECIFICACIONES

Description	Data
Voltage	200 ~ 277 Vac
Ambient temperature	$-55\text{ °C} \leq T_{\text{amb}} \leq 40\text{ °C}$
Minimum installation temperature	-55 °C
Maximum maintain temperature (power on)	65 °C
Maximum exposure temperature (power off)	85 °C
T-rating	T6 (85 °C)
Impact resistance	12 J @ -62 °C
Bus wire	ASTM B355 Class 2 NPC 16 AWG
Dimensions (aprox.)	11B102 11.6 ± 0.2 mm x 5.6 ± 0.2 mm
	11B162 11.6 ± 0.2 mm x 5.6 ± 0.2 mm
	11B242 11.6 ± 0.2 mm x 5.6 ± 0.2 mm
	11B302 13.6 ± 0.2 mm x 5.6 ± 0.2 mm
Minimum bend radius	35 mm @ -62 °C
Standards	EN 60079-0
	EN 60079-7
	EN 60079-30-1

11B (FBL-CP)

SELF REGULATING HEATING CABLE

7. NOMINAL POWER OUTPUT RATING ON METAL PIPES



8. MAXIMUM CIRCUIT LENGTH

Maximum length (m) based on the start-up temperature (°C) and circuit breaker sizes (A). Curve C differential magnetothermic protection. Data considering a supply voltage of 230 Vac.


Model	Start-up Temperature °C	Circuit breaker					
		10A	16A	20A	25A	32A	40A
11B102	-50	62	99	124	132	132	132
	-20	84	134	155	155	155	155
	0	101	162	169	169	169	169
	10	131	193	193	193	193	193
11B162	-50	43	69	87	108	111	111
	-20	59	94	118	129	129	129
	0	71	113	141	142	142	142
	10	92	147	162	162	162	162
11B242	-50	25	40	50	63	81	97
	-20	42	67	84	104	111	111
	0	49	79	99	122	122	122
	10	66	105	131	137	137	137
11B302	-50	1632	26	32	40	52	64
	-20	32	51	64	80	101	101
	0	32	51	64	80	102	113
	10	41	66	82	102	124	124

11B (FBL-CP)





SELF REGULATING HEATING CABLE

9. CABLE CODE


1 1 B 10 2



10. APPROVALS / CERTIFICATIONS

Certification	Certification N.o	Certification	Certification N.o
	IECEX FMG 14.0011X		MRE0000001
	11-AV2BO-0192X		15.10470.296

11. TYPICAL INSTALLATION





TRACELEC
HEATING SOLUTIONS

c/ Josep V. Foix 10 · 43007 Tarragona · Spain
+34 977 290 039 · ofertas@tracelec.es
www.tracelec.es