





240001 (PYEX-EP-SPK-S)

ATEX SPLICE KIT




1. DESCRIPTION



ATEX connection kit for splicing self-regulating heating cables.

2. CONSTRUCTION



Components		
No.	Description	Amount
1	Clamping nut	2
2	Splice body	1
3	Seal	1
4	O-ring	1
5	Connection nipple	1
6	End seal	1
7	Set screw	1

3. FEATURES

This splice kits is designed for the joining of self-regulating heating cables.

It is approved for use in hazardous locations. The enclosure is made of fiberglass reinforced nylon, thermal and mechanical resistant. It is small enough to be installed in tight places or under the insulation.

4. SPECIFICATIONS

Description	Data
Protection level	Ex eb IIC Gb
Protection class	IP66
Min. ambient temperature	-55 °C
Max. exposure temperature	130 °C
Material	Fiberglass reinforced nylon
Standards	IEC60079-0 IEC60079-7
	IEC60529
	IEC60079-30-1
	IEC62395-1

Doc. 240001-1-Rev.01 / 01-23 Pag. 1 of 2

240001 (PYEX-EP-SPK-S)





5. CERTIFICACIONS/ APPROVALS

Certification	Certification no.
C € ₁₁₈₀ (Ex>	Baseefa17ATEX0068X
IECEX	IECEx BAS 17.0053X

Doc. 240001-1-Rev.01 / 01-23 Pag. 2 of 2



www.tracelec.es